Leguan 195.



19.7 m max. working height

9.9 m

250 kg

# The best just got better – now with proven intuitive joystick control.

**INTRODUCING** the next generation in spider lift technology, the Leguan 195 redefines excellence with its unmatched all-terrain capabilities, robust track platform, and impressive driving speeds. Designed to conquer the toughest environments, the 195's advanced boom design delivers maximum side reach even at greater heights, while the cutting-edge joystick control guarantees seamless, precise and safe movements.


Compared to the Leguan 190, the all-new 195 features our user-friendly joystick controls plus quick one-button access to work and home positions. New features also include a shielded boom structure that protects components from external blows, falling branches and sawdust, making the 195 a great choice for arborists and construction workers alike.



# The best just got better – now with proven intuitive joystick control.







#### Standard features.

- 21 hp Kubota diesel engine + 230 V electric motor
- 230 V and USB power outlets on platform
- Automatic engine RPM control
- Automatic start-stop function for electric motor
- Automatic levelling of the outriggers
- Proportional outreach monitoring system
- Electric rotation of the platform
- Home function / Back to work position function
- JIB-boom with 120-degree operating range
- Battery powered emergency lowering system
- Lower controls with integrated service display
- Signal horn

### Optional features.

- Remote control for driving and outriggers
- LED spot lights for platform
- Tool trays on platform
- Outrigger beacons
- Hose to platform (air/water)
- Engine heater
- Non-marking tracks
- Narrow single person platform
- Leguan special trailer

#### **Technical features.**

Max. lift capacity	250 kg (2 persons)
Max. working height	19.7 m
Max. platform height	17.7 m
Max. outreach	9.0 m (250 kg) – 9.9 m (120 kg)
Transport dimensions, L x W x H	5.3 x 1.33 x 2.2 m
Platform dimensions	1.33 x 0.75 m
Rotation of the platform	110° (±55°)
Slewing	440°
Gradeability	45 % (25°)
Dimensions w/o platform, L x W	4.62 x 1.25 m
Outrigger support dimensions	4.08 x 4.08 m
Max. slope for outriggers	25 % (14°)
Weight	2,700 kg
Engine	Kubota 21 hp diesel or 230 V / 2.2 kW electric
Drive system: hydraulic	tracks
Max. drive speed	3.1 km/h

## LEGUÁN'

### Leguan Lifts Oy.

Ylötie 10, 33470 Ylöjärvi FINLAND

www.leguanlifts.com